

Master Craft Industrial Equipment Corp.

333 Southwell Blvd., Tifton, GA 31794

Telephone: (229) 386-0610 • Fax: (229) 382-8482

E-Mail: master@surfsouth.com • Website: www.mastercraftforklift.com**C Series Rough Terrain Forklifts**

The C-Series 2WD and 4WD rough terrain forklifts are made specifically for off road industrial applications. The C-Series 5,000 thru 12,000 lb rough terrain forklifts are powered by the Caterpillar 416E tractor loader backhoe power module. The engine is a C4.4 direct-injected liter turbocharged and charge air cooled engine coupled with a Caterpillar 4 x 4 fully synchromesh transmission, Caterpillar drive axle, and both 2WD and 4WD models comes with a Caterpillar steer axle.

The C-Series 14,000 thru 20,000 lb rough terrain forklifts are powered by a Caterpillar C4.4 direct-injected turbocharged and charge air cooled engine.

All Master Craft forklifts have a 12 month or 2000 hour warranty from defects in material and workmanship. The Caterpillar power train module in the 5,000 thru 12,000 lb forklifts is warranted through Caterpillar by a 2 year or 3000 hour warranty. The 2 year or 3000 hour warranty applies to the engine only for the 14,000 thru 20,000 lb rough terrain forklifts.

Results 1 - 16 of 16

<u>Item #</u>	<u>Lift Capacity @ 24" LC</u>	<u>Mast Height Range</u>	<u>HP</u>	<u>Cubic Engine Capacity</u>	<u>Engine Capacity</u>	<u>Wheel Drive</u>	<u>Standard Mast Tilt</u>	<u>Standard Carriage</u>
C-05-10106	5,000 lb	10-24'	96	N/A	4.4 liters	2WD	38F-9R	60"
C-05-10116	5,000 lb	10-24'	96	N/A	4.4 liters	4WD	38F-9R	60"
C-06-10106	6,000 lb	10-24'	96	N/A	4.4 liters	2WD	38F-9R	60"
C-06-10116	6,000 lb	10-24'	96	N/A	4.4 liters	4WD	38F-9R	60"
C-08-10106	8,000 lb	10-24'	96	N/A	4.4 liters	2WD	38F-9R	60"
C-08-10116	8,000 lb	10-24'	96	N/A	4.4 liters	4WD	38F-9R	60"
C-10-10106	10,000 lb	10-21'	96	N/A	4.4 liters	2WD	38F-9R	60"
C-10-10116	10,000 lb	10-21'	96	N/A	4.4 liters	4WD	38F-9R	60"
C/M-10-10106	10,000 lb	10-21'	96	N/A	4.4 liters	2WD	38F-9R	60"
C/M-10-10116	10,000 lb	10-21'	96	N/A	4.4 liters	4WD	38F-9R	60"
C/M-12-10106	12,000 lb	10-21'	96	N/A	4.4 liters	2WD	38F-9R	60"
C/M-12-10116	12,000 lb	10-21'	96	N/A	4.4 liters	4WD	38F-9R	60"
C-14-974	14,000 lb	12-18'	127	N/A	4.4 liters	4WD	18F-10R	60"
C-16-974	16,000 lb	12-18'	127	N/A	4.4 liters	4WD	18F-10R	60"
C-18-974	18,000 lb	12-16'	127	N/A	4.4 liters	4WD	18F-10R	60"
C-20-974	20,000 lb	12-16'	127	N/A	4.4 liters	4WD	18F-10R	60"

